


- These bottle jack-style toe jacks are loaded with many of the same features as our standard bottle jacks, but the toe-lift feature and swiveling pump handle socket make them ideal for machinery lifting and positioning.
- An internal pressure relief provides added safety by limiting the jack's lifting capability to the capacity of the toe.
- Spring return is an added feature on the larger jacks.
- Swiveling pump handle assembly available on the 5- and 10-ton models. The swiveling jack assembly allows you to access and pump the unit from numerous positions.

Economy TOE JACKS

2, 5 & 10 Ton

Just the power you need at a price you can afford.

CE



							+		
				DIMENSIO	INS				
	A			B					
Order	Ret.	Ext.	Ret.	Ext.	C	D	E	F	
Number	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
J24T	16	140	232	356	47,5	181	51	125	
J55T	25	149	292	476	47,5	257	76,2	184,2	
J106T	32	181	327	476	64	292	100	241	

ORDERING INFORMATION												
	Max Lift		Strokes to	Handle Effort		Metric	Product					
Cap.	Stroke	Order	Extend Pisto	n at Max Load	Carry	tons at	Wt.					
Tons	(mm)	Number	25 mm	(kg)	Handle	700 bar	(kg)					
2	121	J24T	14	19	Yes	1,8	8,3					
5	121	J55T	22	27	Yes	4,5	24					
10	146	J106T	31	33	Yes	9,1	38					