



"C" CLAMPS

5, 10 & 25 TONS




CC10

- In 5, 10 and 25 ton capacities. For use with Power Team general purpose single-acting series cylinders of comparable capacity.
- For clamping, pressing and bending. Ideal for welding and metal fabrication for fit-up of sheet or plate steel.
- Clamps withstand full rated capacity of the cylinders for which they are intended.
- To minimize the effects of off-center loading, the CC5, CC10 and CC25 should be used with the optional 350144 and 350145 swivel caps.

C-Clamps HYDRAULIC

Accessories




Items pictured
at left are:
CC10
C104C
201923

Cap. (tons)	Order Number (C-Clamp only)	Use With Cyl. No.	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (in.)	H (mm)	I (mm)	Weight (kg)
5	CC5	C51C-C57C	314	95,3	186	50,8	63,5	197	1 1/2"-16 UN	22,2	76,2	11,3
10	CC10	C101C-C1010C	403	152,4	240	50,8	85,8	273	2 1/4"-14 UNS	22,2	88,9	20,9
25	CC25	C251C-C2514C	533	152,4	319	76,2	114,3	313	3 5/16"-12 UNS	36,5	117,5	41,3

OPTIONAL ACCESSORIES FOR USE WITH CC5, CC10 & CC25 HYDRAULIC CLAMPS


Swivel Caps



10 ton
350144*
A-35 mm
B-19 mm

25 ton
350145
A-50,8 mm
B-25,4 mm


Threaded Adapters



10 ton
38597
A-1 - 8
B-1 - 8
C-19 mm
D-50,8 mm

25 ton
38953
A-1 1/4-7
B-1 1/2-16
C-70 mm
D-111 mm


Pushing Adapters



10 ton
28228**
A-60,3 mm
B-1 - 8
C-38,1 mm

25 ton
28229**
A-73 mm
B-1 1/4-7
C-44,5 mm


Pushing Adapters



10 ton
201923**
A-79,4 mm
B-57,2 mm
C-136,5 mm
D-12,7 mm
E-1 - 8

25 ton
34510**
A-82,6 mm
B-66,7 mm
C-149 mm
D-19 mm
E-1 1/4-7


Pushing Adapters



10 ton
201454**
A-79,4 mm
B-66,7 mm
C-137 mm
D-19 mm
E-1 - 8

25 ton
34511**
A-82,6 mm
B-66,7 mm
C-149 mm
D-25,4 mm
E-1 1/4-7


V Pushing Adapters



10 ton
34806**
A-66,7 mm
B-1 - 8
C-38,1 mm
D-25,4 mm

25 ton
34807**
A-79,4 mm
B-1 1/4-7
C-44,5 mm
D-31,8 mm

Pushing Adapters



5 ton
309874*
A-51,6 mm
B-562,8 mm
C-15,9 mm

* May be used with CC5

** Must be used with a threaded adapter.