

S CUT 22 / V CUT 22

STARTER WORKSHOP
BENCHTOP

KEY FEATURES

- Smooth bending system
- 90° cut
- Clean cut
- Scalloped blade
- Dust collector included
- Multiple voltage options

CUTTING
MACHINES


1



STANDARD



Scalloped Blade



Dust Collector

TECHNICAL SPECIFICATIONS

CAPACITY	DIMENSIONS
2wb: 1¼" max.	630 x 485 x 650 mm
4ws: 1¼" max.	(25 x 19 x 26 ")
ROTATION SPEED	PACKAGING
3000 rpm	800 x 600 x 830 mm
SCALLOPED BLADE DIAMETER	(31 x 24 x 33")
254 mm (10") included	NET WEIGHT
MAX HOSE OD.	42 kg (93 lb)
50 mm (1.969")	GROSS WEIGHT
MOTOR	42 kg (93 lb)
2.2 kW	TECHNICAL FEATURES
VOLTAGES	Dimensions van type machine:
220/240 V, 3Ph, 50 Hz	488 x 630 x 650 mm
380/415 V, 3Ph, 50 Hz	(19.2 x 24.8 x 25.6");
208/240 V, 3Ph, 60 Hz	38 kg (84 lb)
380/415 V, 3Ph, 60 Hz	
12/24 V also available upon request	

OPTIONAL



Battery & Charger

S CUT 30 E

STARTER & PROFESSIONAL WORKSHOP
BENCHTOP CUTTING MACHINE, OPTIONAL SKIVING

KEY FEATURES

Compact design

Easy and safe to use

Versatile, scalloped blade for high performance and efficient cutting with minimal smoke

Electronic brake

Skiving module can be ordered as optional and integrated on this machine



STANDARD



Scalloped Blade



Dust Collector

TECHNICAL SPECIFICATIONS

CAPACITY

2wb: 2" max.

4ws: 2" max.

6ws: 1 1/4" max.

Industrial: 2" max.

VOLTAGES

220/240 V, 3Ph, 50 Hz

380/415 V, 3Ph, 50 Hz

208/240 V, 3Ph, 60 Hz

380/415 V, 3Ph, 60 Hz

ROTATION SPEED

3000 rpm

DIMENSIONS

835 x 545 x 640 mm

(33 x 21 x 25")

SCALLOPED BLADE DIAMETER

300 mm (11.8")

PACKAGING

1170 x 770 x 1100 mm

MAX HOSE OD.

85 mm (3.346")

(46 x 30 x 43")

MOTOR

2.2 kW

NET WEIGHT

75 kg (165 lb)

GROSS WEIGHT

90 kg (198 lb)

OPTIONAL



Cutting Rail

S CUT 30 L

STARTER & PROFESSIONAL WORKSHOP
STAND TYPE CUTTING MACHINE



KEY FEATURES

- Compact design
- Easy and safe to use
- Versatile, scalloped blade for high performance and efficient cutting with minimal smoke
- Ergonomic, easy to clean
- Integrated dust collector

STANDARD



Smoke Suction
Connector



2 Dust Collectors



Scalloped Blade



Slotted Blade

TECHNICAL SPECIFICATIONS

CAPACITY	VOLTAGES
2wb: 2" max.	220/240 V, 3Ph, 50 Hz
4ws: 2" max.	380/415 V, 3Ph, 50 Hz
6ws: 1¼" max.	208/240 V, 3Ph, 60 Hz
Industrial: 2"	380/415 V, 3Ph, 60 Hz
ROTATION SPEED	DIMENSIONS
3000 rpm	765 x 500 x 1150 mm
SCALLOPED BLADE DIAMETER	(30 x 20 x 45")
254 mm (10")	PACKAGING
MAX HOSE OD.	800 x 600 x 1200 mm
85 mm (3.34")	(32 x 24 x 47")
MOTOR	NET WEIGHT
3.0 kW	92 kg (203 lb)
	GROSS WEIGHT
	120 kg (265 lb)

OPTIONAL



Cutting Rail

S DUO 30

STARTER & PROFESSIONAL WORKSHOP
BENCHTOP, INTEGRATED CUTTING & SKIVING

KEY FEATURES

- Compact design
- Two operations in one machine
- Easy and safe to use
- Versatile, scalloped blade for high performance and efficient cutting with minimal smoke
- Dust free skive operation (drawers for dust collection)
- Electronic brake

STANDARD



Scalloped Blade



2 Dust Collectors

TECHNICAL SPECIFICATIONS

CAPACITY

2wb: 2" max.
4ws: 2" max.
6ws: 1 1/4" max.
Industrial: 2" max.

ROTATION SPEED (CUT)

3000 rpm

ROTATION SPEED (SKIVE)

200 rpm

SCALLOPED BLADE DIAMETER

300 mm (11.8")

MAX HOSE OD.

85 mm (3.34")

MOTOR

2.2 kW

VOLTAGES

220/240 V, 3Ph, 50 Hz
380/415 V, 3Ph, 50 Hz
208/240 V, 3Ph, 60 Hz
380/415 V, 3Ph, 60 Hz

DIMENSIONS

835 x 545 x 640 mm
(33 x 21 x 25")

PACKAGING

1170 x 770 x 1100 mm
46 x 30 x 43"

NET WEIGHT

85 kg (187 lb)

GROSS WEIGHT

100 kg (220 lb)


TECHNICAL FEATURES

Skiving tools for External Skiving (ESE) and for Internal Skiving (IS) to be ordered separately

OPTIONAL



Cutting Rail



Tool Kit ESE



Tool Kit IS

S CUT 55/P


FULL SERVICE WORKSHOP, STARTER PRODUCTION UNITS
STAND TYPE CUTTING MACHINE



STANDARD



Control Panel



Slotted Blade



Feeding Guide



Dust Collector

KEY FEATURES

Versatile, slotted blade for high performance smoke free cutting

Ergonomic and functional design

Double foot pedal system

Safety cover and feeding guides for hose (easy and fast cutting operation)

Digital counter for maintenance assistance

Adjustable speed for cutting on pneumatic version

TECHNICAL SPECIFICATIONS

CAPACITY

2wb: 2" max.

4ws: 2" max.

6ws: 2" max.

Industrial: 2"

ROTATION SPEED

3000 rpm

SLOTTED BLADE DIAMETER

400 mm (15.7")

MAX HOSE OD.

80 mm (3.15")

MOTOR

7.5 kW

VOLTAGES

220/240 V, 3Ph, 50 Hz

380/415 V, 3Ph, 50 Hz

208/240 V, 3Ph, 60 Hz

380/415 V, 3Ph, 60 Hz

DIMENSIONS

1140 x 1000 x 1280 mm

(45 x 39 x 50")

PACKAGING

1600 x 1200 x 1600 mm

(63 x 47 x 63")

NET WEIGHT

240 kg (529 lb)

GROSS WEIGHT

280 kg (617 lb)

TECHNICAL FEATURES

Diameter of the suction connection: 150 mm (6")

Options: Pneumatic bending system, scalloped blade

OPTIONAL



Cutting Rail



Smoke Suction



DV 32



DVC



Decoiler

TS 50


EXPERT SERVICE LINE
STAND TYPE CUTTING MACHINE

KEY FEATURES

- Powerful
- Safety cover
- High visibility
- Suitable for cutting large bore hoses



STANDARD



Slotted Blade

OPTIONAL

TECHNICAL SPECIFICATIONS

CAPACITY

2wb: 3" max.

4ws: 2" max.

6ws: 2" max.

ROTATION SPEED

3000 rpm

SLOTTED BLADE DIAMETER

520 mm (20.5") included

MAX HOSE OD.

125 mm (5")

MOTOR

7.5 kW

VOLTAGES

220/240 V, 3Ph, 50 Hz

380/415 V, 3Ph, 50 Hz

208/240 V, 3Ph, 60 Hz

380/415 V, 3Ph, 60 Hz

DIMENSIONS

910 x 820 x 1280 mm

(36 x 32 x 50")

NET WEIGHT

215 kg (474 lb)

TECHNICAL FEATURES

Diameter of suction connection: 110 mm (4.33")

Optional tool: Brake motor, slotted disc



Cutting Rail



Decoiler



DV 32



DVC

P CUT 90

EXPERT SERVICE LINE
STAND TYPE CUTTING MACHINE

KEY FEATURES

- Very powerful
- Heavy duty for difficult cuts
- Hydraulic bending
- Brake motor
- Electronic soft start
- Smoke suction integrated in cutting table



STANDARD



Slotted Blade



Production Counters



Smoke Suction
Connector



CME Electrical Foot
Switch

TECHNICAL SPECIFICATIONS

CAPACITY

- 2wb: 3½" max.
- 4ws: 3½" max.
- 6ws: 3" max.

ROTATION SPEED

3000 rpm

SLOTTED BLADE DIAMETER

520 mm (20.5") included

MAX HOSE OD.

125 mm (5")

MOTOR

9.0 kW

TECHNICAL FEATURES

- Diameter of suction connection: 110 mm (4.33")
- Standard tool: Hydraulic bending, brake motor
- Optional tool: Slotted disc

VOLTAGES

- 220/240 V, 3Ph, 50 Hz
- 380/415 V, 3Ph, 50 Hz
- 208/240 V, 3Ph, 60 Hz
- 380/415 V, 3Ph, 60 Hz

DIMENSIONS

1000 x 1060 x 1350 mm
(39 x 42 x 53")

NET WEIGHT

260 kg (573 lb)

OPTIONAL



Cutting Rail



Decoiler



DV 32



DVC