


// A55001 - FEMMINA BSPP SV. 60° CON O'RING - DKOR
// BSPP FEMALE 60° CONE WITH O'RING - DKOR



Code	Nut Type	ID			F1		C	CH1
		Dash	mm	In	Dash size	F1		
A55001-02-03	CR	03	5,0	3/16"	02	1/8-28	14,3	14,0
A55001-04-03	SN	03	5,0	3/16"	04	1/4-19	20,3	19,0
A55001-02-04	CR	04	6,0	1/4"	02	1/8-28	14,7	14,0
A55001-04-04	SN	04	6,0	1/4"	04	1/4-19	20,8	19,0
A55001-06-04	SN	04	6,0	1/4"	06	3/8-19	23,3	22,0
A55001-04-05	CR	05	8,0	5/16"	04	1/4-19	17,3	19,0
A55001-06-05	SN	05	8,0	5/16"	06	3/8-19	23,3	22,0
A55001-04-06	CR	06	10,0	3/8"	04	1/4-19	17,3	19,0
A55001-06-06	SN	06	10,0	3/8"	06	3/8-19	23,3	22,0
A55001-08-06	SN	06	10,0	3/8"	08	1/2-14	24,3	27,0
A55001-06-08	CR	08	13,0	1/2"	06	3/8-19	18,6	22,0
A55001-08-08	SN	08	13,0	1/2"	08	1/2-14	25,1	27,0
A55001-10-08	SN	08	13,0	1/2"	10	5/8-14	28,4	27,0
A55001-12-08	SN	08	13,0	1/2"	12	3/4-14	29,0	32,0
A55001-10-10	CR	10	16,0	5/8"	10	5/8-14	17,1	27,0
A55001-12-10	SN	10	16,0	5/8"	12	3/4-14	29,0	32,0
A55001-12-12	CR	12	19,0	3/4"	12	3/4-14	23,9	32,0
A55001-16-12	SN	12	19,0	3/4"	16	1-11	34,0	38,0
A55001-16-16	CR	16	25,0	1"	16	1-11	23,9	38,0
A55001-20-16	SN	16	25,0	1"	20	1 1/4-11	39,4	50,0
A55001-20-20	TN	20	32,0	1 1/4"	20	1 1/4-11	32,0	50,0
A55001-24-20	SN	20	32,0	1 1/4"	24	1 1/2-11	41,9	55,0
A55001-24-24	TN	24	38,0	1 1/2"	24	1 1/2-11	33,8	55,0
A55001-32-24	SN	24	38,0	1 1/2"	32	2-11	47,0	70,0
A55001-32-32	TN	32	51,0	2"	32	2-11	34,0	70,0