

CARBOFLEX (340 30)



IT IMPIEGO

Tubo in gomma spiralato greco idoneo per aspirazione e mandata di olii e carburanti.

- **TEMPERATURA:** -35°C +80°C

STRUTTURA

- **Sottostrato:** liscio in gomma nera NBR resistente ai prodotti petroliferi con un contenuto aromatico non superiore al 50%.
- **Rinforzi:** spirale metallica incorporata con tessuti sintetici ad alta resistenza.
- **Copertura:** in gomma nera CR/NBR resistente all'abrasione, agli agenti atmosferici e all'ozono, olii.
- **Superficie:** greca ad impressione tela.
- **Marcatura:** listino scritta rossa "H.T. - FUEL & OIL S&D W.P. 5 BAR (75 PSI)".

EN APPLICATION

Herdwall square corrugated cover rubber hose suitable for suction and delivery of oils and fuels.

- **TEMPERATURE RANGE:** -35°C +80°C

CONSTRUCTION

- **Tube:** black, smooth, petroleum products up to 50% aromatic content resistant NBR rubber.
- **Reinforcement:** steel wire helix with high strength synthetic textile plies.
- **Cover:** black, abrasion, weathering and ozone resistant CR/NBR rubber, oil.
- **Surface:** square corrugated fabric finished.
- **Branding:** red transfer tape lettering "H.T. - FUEL & OIL S&D W.P. 5 BAR (75 PSI)".

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESS. SCOPPIO BURST PRESSURE		RAGGIO DI CURVATURA BENDING RADIUS		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mm	inch	mt	ft
20	25/32"	30	1.3/16"	0.61	0.41	5	75	15	225	60	2.36"	20	65.5
25	1"	35	1.3/8"	0.69	0.46	5	75	15	225	75	2.95"	20	65.5
30	1.3/16"	40	1.9/16"	0.75	0.50	5	75	15	225	90	3.54"	20	65.5
32	1.1/4"	42	1.21/32"	0.87	0.58	5	75	15	225	100	3.94"	20	65.5
35	1.3/8"	45	1.3/4"	1.00	0.67	5	75	15	225	105	4.13"	20	65.5
38	1.1/2"	48	1.7/8"	1.05	0.70	5	75	15	225	115	4.53"	20	65.5
40	1.9/16"	50	1.31/32"	1.10	0.74	5	75	15	225	120	4.72"	20	65.5
45	1.3/4"	55	2.5/32"	1.20	0.80	5	75	15	225	135	5.31"	20	65.5
51	2"	61	2.13/32"	1.40	0.94	5	75	15	225	155	6.10"	20	65.5
60	2.3/8"	70	2.3/4"	1.70	1.14	5	75	15	225	185	7.28"	20	65.5
76	3"	90	3.19/32	2.70	1.81	5	75	15	225	200	7.87"	20	65.5
90	3.17/32"	104	4"	3.36	2.25	5	75	15	225	300	11.81"	20	65.5

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.