

108

ABRASIVI



- **TEMPERATURA:** -40°C +70°C

- **Sottostrato:** liscio in gomma nera NR/SBR antistatica resistente all'abrasione.
- **Rinforzi:** tessuti sintetici ad alta resistenza.
- **Copertura:** in gomma nera NR/SBR antistatica resistente all'abrasione e agli agenti atmosferici.
- **Superficie:** liscia ad impressione tela.
- **Marchatura:** listino scritto giallo "H.T. - CEMENTUB - TRUCK HOSE - ITALY".

CEMENTUB/PA Sottostrato in gomma para beige.
CEMENTUB/SP10L con spirale in acciaio.
CEREALI/10 Sottostrato atossico bianco.

- **TEMPERATURE RANGE:** -40°C +70°C

- **Tube:** black, smooth antistatic NR/SBR rubber abrasion resistant.
- **Reinforcement:** high strength synthetic textile plies.
- **Cover:** black, abrasion and weathering resistant antistatic NR/SBR rubber.
- **Surface:** smooth fabric finished.
- **Branding:** yellow transfer tape lettering "H.T. - CEMENTUB - TRUCK HOSE - ITALY".

CEMENTUB/PA beige natural rubber Tube.
CEMENTUB/SP10L with steel wire.
CEREAL/10 white non toxic Tube.

[illegible]

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.