# SCAMO/SP/NAJ (355 65)






## IT IMPIEGO

**Tubo in gomma spiralato liscio** idoneo per scarico gas combusti e raffreddamento degli scambiatori di calore sulle imbarcazioni da diporto entro i 24 mt.

*Normative di riferimento* **SAE J 2006:2003 R2 - ISO 13363:2004 Tipo 2 Classe B.**

*Tubo omologato:* **LLOYD'S REGISTER N. 96/00126 - R.I. NA N. DIP 075110CS**

- **TEMPERATURA:** -30°C +100°C

## STRUTTURA

- **Sottostrato**: liscio in gomma nera resistente ai gas combusti e all'acqua di mare.
- **Rinforzi**: spirale metallica incorporata con filati sintetici ad alta resistenza.
- **Copertura**: in gomma nera resistente all'abrasione, al calore ed agli agenti marini.
- **Superficie**: liscia ad impressione tela.
- **Marcatura**: listino verde " Italy SCAMO/SP MARINE WET EXHAUST - LLOYD'S REGISTER N. 96/00126 - RINA N. DIP 075110CS" listino a rilievo "SAE J 2006:03 R2 - ISO 13363:04 TYPE 2 CLASS B - d.i. q.le anno".

## EN APPLICATION

**Hardwall smooth cover marine exhaust rubber hose** used also for cooling the heat exchangers on pleasure boats up to 24 mt.

*Standards:* **SAE J 2006:03 R2-ISO 13363:04 Type 2 Classe B.**

*Approved:* **LLOYD'S REGISTER N. 96/00126 - R.I.NA N. DIP 075110CS**

- **TEMPERATURE RANGE:** -30°C +100

## CONSTRUCTION

- **Tube**: black, smooth marine exhaust and sea water resistant rubber.
- **Reinforcement**: steel wire helix and high strength synthetic textile yarn.
- **Cover**: black, abrasion, heat and marine agents resistant rubber.
- **Surface**: smooth fabric finished.
- **Branding**: green transfer tape " Italy SCAMO/SP MARINE WET EXHAUST - LLOYD'S REGISTER N. 96/00126 RINA N. DIP 075110CS" embossed "SAE J 2006:03 R2 ISO 13363:04 TYPE 2 CLASS - i.d. q.le year".

| DIAMETRO INTERNO INSIDE DIAMETER | | SPESSORE TICHNESS | | PESO TEORICO WEIGHT | | PRESSIONE ESERCIZIO WORKING PRESSURE | | RAGGIO CURVATURA BENDING RADIUS | | LUNGHEZZA LENGTH | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | inch | mm | inch | kg/mt | lbs/ft | bar | psi | mm | inch | mt | ft |
| 19 | 3/4" | 4.5 | 0.18" | 0.44 | 0.30 | 3 | 45 | 57 | 2.24" | 20 | 65.5 |
| 25 | 1" | 4.5 | 0.18" | 0.50 | 0.34 | 3 | 45 | 75 | 3.00" | 20 | 65.5 |
| 30 | 1.3/16" | 4.5 | 0.18" | 0.58 | 0.39 | 3 | 45 | 90 | 3.66" | 20 | 65.5 |
| 32 | 1.1/4" | 4.5 | 0.18" | 0.62 | 0.42 | 3 | 45 | 96 | 3.77" | 20 | 65.5 |
| 35 | 1.3/8" | 4.5 | 0.18" | 0.66 | 0.44 | 3 | 45 | 105 | 4.13" | 20 | 65.5 |
| 38 | 1.1/2" | 4.5 | 0.18" | 0.72 | 0.48 | 3 | 45 | 114 | 4.49" | 20 | 65.5 |
| 40 | 1.9/16" | 4.5 | 0.18" | 0.75 | 0.50 | 3 | 45 | 120 | 4.72" | 20 | 65.5 |
| 45 | 1.3/4" | 4.5 | 0.18" | 0.84 | 0.56 | 3 | 45 | 135 | 5.31" | 20 | 65.5 |
| 51 | 2" | 5 | 0.20" | 0.96 | 0.64 | 3 | 45 | 150 | 5.91" | 20 | 65.5 |
| 60 | 2.3/8" | 5 | 0.20" | 1.35 | 0.91 | 3 | 45 | 180 | 7.09" | 20 | 65.5 |
| 63.5 | 2.1/2" | 5 | 0.20" | 1.40 | 0.93 | 3 | 45 | 185 | 7.58" | 20 | 65.5 |

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.