

S CRIMP 350 EVO / S CRIMP 350 L



FULL SERVICE WORKSHOP **BENCHTOP; VERY HIGH CRIMP FORCE**

KEY FEATURES

Crimp force of up to 350 tonnes for hoses up to 3"

Easy to use and robust

Automatic maintenance alerts

Groove for 90° long drop fittings

Also available as S CRIMP 350 L with 4.0 kW motor

Model shown equipped with SCS control panel

CONTROL OPTIONS AVAILABLE ON REQUEST

TECHNICAL SPECIFICATIONS

CAPACITY*	NOISE LEVEL	
2wb: 3" max.	<70 dB A	
Textile / Suction Hose: 4" max.	MOTOR	
4ws: 2" max.	5.5 kW / 4 kW	
6ws: 2" max.	VOLTAGES	
CRIMP RANGE	220/240 V, 3Ph, 50 Hz	
4 - 130 mm (0.157 - 5.118")	380/415 V, 3Ph, 50 Hz	
CRIMP FORCE	208/240 V, 3Ph, 60 Hz	
350 t	380/415 V, 3Ph, 60 Hz	
OPENING WITH DIES	DIMENSIONS	
+54 mm (+2.125")	765 x 400 x 750 mm	
COMPLETE OPENING	(30 x 16 x 30")	
180 mm (7.086")	NET WEIGHT	
MASTER DIE LENGTH	262 kg (578 lb)	
115 mm (4.523")	TECHNICAL FEATURES	
STANDARD DIES	-Automatic maintenance alerts	
15, 18, 21, 24, 27, 30, 33, 36, 39, 42, 45, 48, 51, 57, 62, 66, 70, 73, 76	-Cylinder protection against dust - durable design -Also available as S CRIMP 350 EVO L with 4.0 kW Motor	

*Indicative capacities depending on hose and fitting type

sc OPTIONAL	SCE	scs
GREEN Y		
Mainten	ance Kit	Marking Dies
		6
Die Storage Panel	Die Storage Table	Electrical Footswitch

Aluminium Quick Change Gun

Quick Change

Gun

Die Sets for Brake

& Air Conditioning

Hoses





Bluetooth

1.00

Mechanical Backstop



Die Storage Panel EVO