

// RITORNO OLIO

// OIL RETURN

// DH 605T



// EXCEED SAE 100 R4

Tubo: gomma sintetica resistente agli oli.

Rinforzo: trecce tessili ad alta tenacità con spirale d'acciaio incorporata.

Copertura: gomma sintetica resistente all'abrasione, all'ozono e agli idrocarburi.

Applicazioni: progettato per sistemi idraulici di aspirazione e mandata oli e carburanti e applicazioni industriali generali.

Esercizio costante: -30 °C +80 °C

Lunghezza: 61 m max

Tube: oil resistant synthetic rubber.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: abrasion, ozone and hydrocarbon resistant synthetic rubber.

Applications: specially designed for hydraulic oil suction and delivery systems and fuels and general industrial applications.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

Length: 61 m max

Code												
	mm	In	mm	In	Mpa	psi	Mpa	psi	mm	Vacuum (%)	Kg/m	lb/ft
DH 605T-019	19,0	3/4"	29,00	1,14	1,0	150	3,0	450	76,0	100	0,610	0,41
DH 605T-025	25,0	1"	35,00	1,38	1,0	150	3,0	450	100,0	100	0,760	0,52
DH 605T-030	30,0	1 3/16"	40,00	1,57	1,0	150	3,0	450	120,0	100	0,850	0,58
DH 605T-032	32,0	1 1/4"	42,00	1,62	1,0	150	3,0	450	128,0	100	0,900	0,62
DH 605T-035	35,0	1 3/8"	45,00	1,77	1,0	150	3,0	450	140,0	100	0,980	0,67
DH 605T-038	38,0	1 1/2"	48,00	1,89	1,0	150	3,0	450	152,0	100	1,050	0,72
DH 605T-040	40,0	1 9/16"	50,00	1,97	1,0	150	3,0	450	160,0	100	1,090	0,75
DH 605T-042	42,0	1 5/8"	52,00	2,04	1,0	150	3,0	450	168,0	100	1,150	0,79
DH 605T-045	45,0	1 3/4"	55,00	2,16	1,0	150	3,0	450	180,0	100	1,220	0,83
DH 605T-048	48,0	1 7/8"	58,00	2,28	1,0	150	3,0	450	192,0	100	1,280	0,87
DH 605T-051	51,0	2"	61,00	2,40	1,0	150	3,0	450	204,0	100	1,350	0,92
DH 605T-057	57,0	2 1/4"	67,00	2,64	1,0	150	3,0	450	228,0	100	1,510	1,02
DH 605T-060	60,0	2 3/8"	72,00	2,84	1,0	150	3,0	450	240,0	100	2,020	1,38
DH 605T-063	63,0	2 1/2"	75,00	2,95	1,0	150	3,0	450	252,0	90	2,110	1,44
DH 605T-070	70,0	2 3/4"	82,00	3,23	1,0	150	3,0	450	280,0	90	2,350	1,61
DH 605T-076	76,0	3"	88,00	3,46	1,0	150	3,0	450	304,0	90	2,520	1,73
DH 605T-080	80,0	3 1/8"	94,00	3,70	1,0	150	3,0	450	320,0	90	2,700	1,85
DH 605T-090	90,0	3 1/2"	104,00	4,09	1,0	150	3,0	450	360,0	90	3,140	2,15
DH 605T-102	102,0	4"	116,00	4,57	1,0	150	3,0	450	408,0	90	3,500	2,40
DH 605T-110	110,0	4 5/16"	124,00	4,88	1,0	150	3,0	450	440,0	90	4,240	2,90
DH 605T-115	115,0	4 1/2"	129,00	5,08	1,0	150	3,0	450	460,0	90	4,410	3,02
DH 605T-120	120,0	4 3/4"	138,00	5,43	1,0	150	3,0	450	480,0	80	5,640	3,86
DH 605T-127	127,0	5"	145,00	5,71	1,0	150	3,0	450	508,0	80	5,930	4,06
DH 605T-133	133,0	5 1/4"	151,00	5,94	1,0	150	2,5	375	532,0	80	6,170	4,27
DH 605T-152	152,0	6"	170,00	6,70	1,0	150	2,5	375	608,0	80	7,360	5,04
DH 605T-203	203,0	8"	225,00	8,85	1,0	150	2,5	375	812,0	70	11,700	8,02

// DH 634



// EXTRA FLEXIBLE - SAE 100 R4

Tubo: gomma sintetica resistente agli oli.

Rinforzo: trecce tessili ad alta tenacità con spirale d'acciaio incorporata.

Copertura: gomma sintetica resistente all'abrasione, all'ozono e agli idrocarburi.

Applicazioni: progettato per sistemi idraulici di aspirazione e mandata oli e carburanti e applicazioni industriali generali.

Esercizio costante: -40 °C +100 °C

Lunghezza: 61 m max

Tube: oil resistant synthetic rubber.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: abrasion, ozone and hydrocarbon resistant synthetic rubber.

Applications: specially designed for hydraulic oil suction and delivery systems and fuels and general industrial applications.

Constant operation: -40 °C +100 °C (-40 °F +212 °F)

Length: 61 m max

Code													
	Dash	mm	In	mm	In	Mpa	psi	Mpa	psi	mm	In	Kg/m	lb/ft
DH 634-012	12	19,0	3/4"	30,00	1,18	2,1	300	8,4	1200	38,0	1,50	0,600	0,41
DH 634-016	16	25,0	1"	36,00	1,42	1,7	250	6,8	986	50,0	1,97	0,750	0,51
DH 634-020	20	32,0	1 1/4"	43,00	1,69	1,4	200	5,6	800	64,0	2,52	0,920	0,62
DH 634-024	24	38,0	1 1/2"	49,00	1,93	1,0	150	4,0	600	76,0	2,99	1,060	0,72
DH 634-032	32	51,0	2"	62,00	2,44	0,7	100	2,8	400	102,0	4,02	1,380	0,93
DH 634-040	40	63,0	2 1/2"	76,00	2,99	0,4	60	1,6	240	125,0	4,92	2,180	1,47
DH 634-048	48	76,0	3"	89,00	3,50	0,4	60	1,6	240	152,0	5,98	2,590	1,75
DH 634-064	64	102,0	4"	116,00	4,57	0,2	30	0,8	120	203,0	7,99	3,400	2,29