

## // A55053 - FEMMINA 90° JIC SV. 37° SHORT DROP -DKJ 90S CON DADO A PRESSARE



## // A55G53 - FEMMINA 90° JIC SV. 37° SHORT DROP -DKJ 90S CON DOPPIO ESAGONO E DADO BATTUTA



Code	Nut Type	ID			F1		С	D Drop	СН	CH1	
		Dash	mm	In	Dash Size	F1	mm	mm	mm	mm	
A55053-04-03	CR	03	5,0 mm	3/16"	04	7/16-20	26,7 mm	21,0 mm		16,0 mm	
\$55053-04-04	CR	04	6,0 mm	1/4"	04	7/16-20	27,0 mm	21,0 mm		16,0 mm	
55G53-04-04	SN	04	6,0 mm	1/4"	04	7/16-20	27,0 mm	21,0 mm	14,0 mm	14,0 mm	
55053-05-04	CR	04	6,0 mm	1/4"	05	1/2-20	26,5 mm	23,5 mm		17,0 mm	
55G53-05-04	SN	04	6,0 mm	1/4"	05	1/2-20	26,5 mm	21,0 mm	14,0 mm	17,0 mm	
55053-06-04	CR	04	6,0 mm	1/4"	06	9/16-18	31,0 mm	23,0 mm		19,0 mm	
55G53-06-04	SN	04	6,0 mm	1/4"	06	9/16-18	30,7 mm	23,0 mm	14,0 mm	19,0 mm	
55053-06-05	CR	05	8,0 mm	5/16"	06	9/16-18	42,7 mm	23,0 mm		19,0 mm	
55G53-06-05	SN	05	8,0 mm	5/16"	06	9/16-18	41,0 mm	23,0 mm	14,0 mm	19,0 mm	
55053-05-06	CR	06	10,0 mm	3/8"	05	1/2-20	33,3 mm	25,0 mm		17,0 mm	
55053-06-06	CR	06	10,0 mm	3/8"	06	9/16-18	42,3 mm	25,0 mm		19,0 mm	
55G53-06-06	SN	06	10,0 mm	3/8"	06	9/16-18	40,3 mm	24,5 mm	17,0 mm	19,0 mm	
55053-08-06	CR	06	10,0 mm	3/8"	08	3/4-16	48,8 mm	29,0 mm		25,0 mm	
55G53-08-06	SN	06	10,0 mm	3/8"	08	3/4-16	48,8 mm	29,0 mm	17,0 mm	22,0 mm	
55053-08-08	CR	08	13,0 mm	1/2"	08	3/4-16	46,4 mm	29,0 mm		25,0 mm	
55G53-08-08	SN	08	13,0 mm	1/2"	08	3/4-16	46,0 mm	29,0 mm	19,0 mm	22,0 mm	
55053-10-08	CR	08	13,0 mm	1/2"	10	7/8-14	45,8 mm	32,0 mm		27,0 mm	
55G53-10-08	SN	08	13,0 mm	1/2"	10	7/8-14	46,0 mm	32,0 mm	19,0 mm	27,0 mm	
55053-12-08	CR	08	13,0 mm	1/2"	12	1 1/16-12	37,3 mm	46,0 mm		32,0 mm	
55053-10-10	CR	10	16,0 mm	5/8"	10	7/8-14	36,5 mm	32,0 mm		27,0 mm	
55053-12-10	CR	10	16,0 mm	5/8"	12	1 1/16-12	47,9 mm	48,0 mm		32,0 mm	
55G53-12-10	SN	10	16,0 mm	5/8"	12	1 1/16-12	48,0 mm	48,0 mm	24,0 mm	32,0 mm	
55053-12-12	CR	12	19,0 mm	3/4"	12	1 1/16-12	58,2 mm	46,0 mm		32,0 mm	
55G53-12-12	SN	12	19,0 mm	3/4"	12	1 1/16-12	62,4 mm	48,0 mm	27,0 mm	32,0 mm	
55053-14-12	CR	12	19,0 mm	3/4"	14	1 3/16-12	49,6 mm	52,5 mm		36,0 mm	
55053-16-12	CR	12	19,0 mm	3/4"	16	1 5/16-12	53,6 mm	53,0 mm		38,0 mm	
55G53-16-12	SN	12	19,0 mm	3/4"	16	1 5/16-12	53,6 mm	53,0 mm		41,0 mm	
55053-16-16	CR	16	25,0 mm	1"	16	1 5/16-12	74,0 mm	56,0 mm		38,0 mm	
55G53-16-16	SN	16	25,0 mm	1"	16	1 5/16-12	74,0 mm	56,0 mm	32,0 mm	41,0 mm	1