



// A55054 - FEMMINA 90° JIC SV. 37° - MEDIUM DROP
DKJ 90M CON DADO A PRESSARE// A55G54 - FEMMINA 90° JIC SV. 37° - MEDIUM DROP
DKJ 90M CON DOPPIO ESAGONO E DADO BATTUTA**NEW**

Code	Nut Type	ID			F1	F1	C	D Drop	CH	CH1	
		Dash	mm	In							
A55054-04-03	CR	03	5,0 mm	3/16"	04	7/16-20	33,5 mm	32,0 mm		16,0 mm	
A55054-04-04	CR	04	6,0 mm	1/4"	04	7/16-20	34,2 mm	32,0 mm		16,0 mm	
A55G54-04-04	SN	04	6,0 mm	1/4"	04	7/16-20	34,0 mm	32,0 mm	14,0 mm	14,0 mm	NEW
A55054-05-04	CR	04	6,0 mm	1/4"	05	1/2-20	25,7 mm	30,0 mm		17,0 mm	
A55G54-05-04	SN	04	6,0 mm	1/4"	05	1/2-20	26,0 mm	32,0 mm	14,0 mm	17,0 mm	NEW
A55054-06-04	CR	04	6,0 mm	1/4"	06	9/16-18	28,5 mm	38,0 mm		19,0 mm	
A55G54-06-04	SN	04	6,0 mm	1/4"	06	9/16-18	31,0 mm	38,0 mm		19,0 mm	NEW
A55054-05-05	CR	05	8,0 mm	5/16"	05	1/2-20	34,2 mm	32,0 mm		17,0 mm	
A55G54-05-05	SN	05	8,0 mm	5/16"	05	1/2-20	34,0 mm	32,0 mm	14,0 mm	17,0 mm	NEW
A55054-06-05	CR	05	8,0 mm	5/16"	06	9/16-18	33,2 mm	35,0 mm		19,0 mm	
A55G54-06-05	SN	05	8,0 mm	5/16"	06	9/16-18	33,0 mm	35,0 mm	14,0 mm	19,0 mm	NEW
A55054-06-06	CR	06	10,0 mm	3/8"	06	9/16-18	31,3 mm	35,0 mm		19,0 mm	
A55G54-06-06	SN	06	10,0 mm	3/8"	06	9/16-18	31,3 mm	38,0 mm	17,0 mm	19,0 mm	NEW
A55054-08-06	CR	06	10,0 mm	3/8"	08	3/4-16	39,5 mm	41,0 mm		25,0 mm	
A55G54-08-06	SN	06	10,0 mm	3/8"	08	3/4-16	39,5 mm	41,0 mm		22,0 mm	NEW
A55054-10-06	CR	06	10,0 mm	3/8"	10	7/8-14	44,6 mm	47,0 mm		27,0 mm	
A55054-08-08	CR	08	13,0 mm	1/2"	08	3/4-16	37,2 mm	40,0 mm		25,0 mm	
A55G54-08-08	SN	08	13,0 mm	1/2"	08	3/4-16	37,2 mm	41,0 mm	19,0 mm	22,0 mm	NEW
A55054-10-08	CR	08	13,0 mm	1/2"	10	7/8-14	43,3 mm	47,0 mm		27,0 mm	
A55G54-10-08	SN	08	13,0 mm	1/2"	10	7/8-14	43,3 mm	47,0 mm	19,0 mm	27,0 mm	NEW
A55054-10-10	CR	10	16,0 mm	5/8"	10	7/8-14	49,4 mm	48,0 mm		27,0 mm	
A55G54-10-10	SN	10	16,0 mm	5/8"	10	7/8-14	49,4 mm	47,0 mm	24,0 mm	27,0 mm	NEW
A55054-12-10	CR	10	16,0 mm	5/8"	12	1 1/16-12	47,9 mm	58,0 mm		32,0 mm	
A55G54-12-10	SN	10	16,0 mm	5/8"	12	1 1/16-12	48,0 mm	58,0 mm	24,0 mm	32,0 mm	NEW
A55054-12-12	CR	12	19,0 mm	3/4"	12	1 1/16-12	52,4 mm	54,0 mm		32,0 mm	
A55G54-12-12	SN	12	19,0 mm	3/4"	12	1 1/16-12	52,0 mm	58,0 mm	27,0 mm	32,0 mm	NEW
A55054-16-12	CR	12	19,0 mm	3/4"	16	1 5/16-12	52,6 mm	72,0 mm		38,0 mm	
A55G54-16-12	SN	12	19,0 mm	3/4"	16	1 5/16-12	52,6 mm	71,0 mm		41,0 mm	
A55054-16-16	CR	16	25,0 mm	1"	16	1 5/16-12	72,6 mm	71,5 mm		38,0 mm	
A55G54-16-16	SN	16	25,0 mm	1"	16	1 5/16-12	73,0 mm	71,0 mm	32,0 mm	41,0 mm	NEW
A55054-20-16	Thrust wire nut	16	25,0 mm	1"	20	1 5/8-12	72,6 mm	78,0 mm		50,0 mm	
A55054-20-20	Thrust wire nut	20	32,0 mm	1 1/4"	20	1 5/8-12	82,4 mm	78,0 mm		50,0 mm	
A55054-24-20	Thrust wire nut	20	32,0 mm	1 1/4"	24	1 7/8-12	87,3 mm	82,0 mm		55,0 mm	
A55054-24-24	Thrust wire nut	24	38,0 mm	1 1/2"	24	1 7/8-12	95,3 mm	92,0 mm		55,0 mm	
A55054-32-32	Thrust wire nut	32	51,0 mm	2"	32	2 1/2-12	129,5 mm	140,0 mm		70,0 mm	