
// A55055 - FEMMINA 90° JIC SV. 37° - LONG DROP DKJ 90L CON DADO A PRESSARE



// A55G55 - FEMMINA 90° JIC SV. 37° - LONG DROP DKJ 90L CON DOPPIO ESAGONO E DADO BATTUTA



	CH1 mm	CH mm	D Drop mm	C mm	F1	F1	ID				0-1-
						Dash Size	In	mm	Dash	Nut Type	Code
	16,0 mm		46,0 mm	30,8 mm	7/16-20	04	1/4"	6,0 mm	04	CR	A55055-04-04
	14,0 mm	14,0 mm	46,0 mm	31,0 mm	7/16-20	04	1/4"	6,0 mm	04	SN	A55G55-04-04
	17,0 mm		45,0 mm	31,3 mm	1/2-20	05	1/4"	6,0 mm	04	CR	A55055-05-04
	17,0 mm	14,0 mm	46,0 mm	31,0 mm	1/2-20	05	1/4"	6,0 mm	04	SN	A55G55-05-04
	19,0 mm		54,0 mm	43,3 mm	9/16-18	06	3/8"	10,0 mm	06	CR	A55055-06-06
	17,0 mm	17,0 mm	54,0 mm	43,3 mm	9/16-18	06	3/8"	10,0 mm	06	SN	A55G55-06-06
	25,0 mm		64,0 mm	46,8 mm	3/4-16	08	3/8"	10,0 mm	06	CR	A55055-08-06
	22,0 mm		64,0 mm	47,0 mm	3/4-16	08	3/8"	10,0 mm	06	SN	A55G55-08-06
	25,0 mm		64,0 mm	49,9 mm	3/4-16	08	1/2"	13,0 mm	08	CR	A55055-08-08
	22,0 mm	19,0 mm	64,0 mm	49,9 mm	3/4-16	08	1/2"	13,0 mm	08	SN	A55G55-08-08
	27,0 mm		65,0 mm	37,3 mm	7/8-14	10	1/2"	13,0 mm	08	CR	A55055-10-08
	27,0 mm	19,0 mm	65,0 mm	37,2 mm	7/8-14	10	1/2"	13,0 mm	08	SN	A55G55-10-08
	27,0 mm		65,0 mm	49,9 mm	7/8-14	10	5/8"	16,0 mm	10	CR	A55055-10-10
	27,0 mm	24,0 mm	70,0 mm	50,0 mm	7/8-14	10	5/8"	16,0 mm	10	SN	A55G55-10-10
	32,0 mm		95,0 mm	54,1 mm	1 1/16-12	12	3/4"	19,0 mm	12	CR	A55055-12-12
	32,0 mm	27,0 mm	96,0 mm	54,0 mm	1 1/16-12	12	3/4"	19,0 mm	12	SN	A55G55-12-12
	38,0 mm		114,0 mm	78,6 mm	1 5/16-12	16	1"	25,0 mm	16	CR	A55055-16-16
	41,0 mm	32,0 mm	114,0 mm	79,0 mm	1 5/16-12	16	1"	25,0 mm	16	SN	A55G55-16-16