



// A55064 - FEMMINA 45° JIC SV. 37° SEAT - DKJ  
45M CON DADO A PRESSARE



// A55G64 - FEMMINA 45° JIC SV. 37° SEAT - DKJ  
45M CON DOPPIO ESAGONO E DADO A BATTUTA



NEW

RACCORDI OLEODINAMICI HYDRAULIC FITTINGS

Code	Nut Type	ID			F1		C	D Drop	CH	CH1	
		Dash	mm	In	Dash Size	F1					
A55064-04-03	CR	03	5,0 mm	3/16"	04	7/16-20	37,1 mm	10,0 mm		16,0 mm	
A55064-04-04	CR	04	6,0 mm	1/4"	04	7/16-20	36,6 mm	10,0 mm		16,0 mm	
A55G64-04-04	SN	04	6,0 mm	1/4"	04	7/16-20	37,0 mm	10,0 mm	14,0 mm	14,0 mm	NEW
A55064-05-04	CR	04	6,0 mm	1/4"	05	1/2-20	37,2 mm	12,0 mm		17,0 mm	
A55064-06-04	CR	04	6,0 mm	1/4"	06	9/16-18	39,4 mm	11,0 mm		19,0 mm	
A55G64-06-04	SN	04	6,0 mm	1/4"	06	9/16-18	39,4 mm	11,0 mm	14,0 mm	19,0 mm	NEW
A55064-05-05	CR	05	8,0 mm	5/16"	05	1/2-20	39,8 mm	12,0 mm		17,0 mm	
A55G64-05-05	SN	05	8,0 mm	5/16"	05	1/2-20	40,0 mm	11,0 mm	14,0 mm	17,0 mm	NEW
A55064-06-05	CR	05	8,0 mm	5/16"	06	9/16-18	42,8 mm	12,0 mm		19,0 mm	
A55064-06-06	CR	06	10,0 mm	3/8"	06	9/16-18	46,3 mm	11,0 mm		19,0 mm	
A55G64-06-06	SN	06	10,0 mm	3/8"	06	9/16-18	46,0 mm	11,0 mm	17,0 mm	19,0 mm	NEW
A55064-08-06	CR	06	10,0 mm	3/8"	08	3/4-16	47,2 mm	15,0 mm		25,0 mm	
A55G64-08-06	SN	06	10,0 mm	3/8"	08	3/4-16	47,0 mm	22,0 mm	17,0 mm	22,0 mm	NEW
A55064-08-08	CR	08	13,0 mm	1/2"	08	3/4-16	51,6 mm	15,0 mm		25,0 mm	
A55G64-08-08	SN	08	13,0 mm	1/2"	08	3/4-16	52,0 mm	15,0 mm	19,0 mm	22,0 mm	NEW
A55064-10-08	CR	08	13,0 mm	1/2"	10	7/8-14	50,7 mm	16,0 mm		27,0 mm	
A55G64-10-08	SN	08	13,0 mm	1/2"	10	7/8-14	51,0 mm	16,0 mm	19,0 mm	27,0 mm	NEW
A55064-12-08	CR	08	13,0 mm	1/2"	12	1 1/16-12	57,0 mm	21,0 mm		32,0 mm	
A55064-10-10	CR	10	16,0 mm	5/8"	10	7/8-14	62,2 mm	19,0 mm		27,0 mm	
A55G64-10-10	SN	10	16,0 mm	5/8"	10	7/8-14	63,4 mm	16,0 mm	24,0 mm	27,0 mm	NEW
A55064-12-10	CR	10	16,0 mm	5/8"	12	1 1/16-12	68,6 mm	21,0 mm		32,0 mm	
A55G64-12-10	SN	10	16,0 mm	5/8"	12	1 1/16-12	69,0 mm	21,0 mm	24,0 mm	32,0 mm	NEW
A55064-12-12	CR	12	19,0 mm	3/4"	12	1 1/16-12	67,5 mm	21,0 mm		32,0 mm	
A55G64-12-12	SN	12	19,0 mm	3/4"	12	1 1/16-12	67,0 mm	21,0 mm	27,0 mm	32,0 mm	NEW
A55064-14-12	CR	12	19,0 mm	3/4"	14	1 3/16-12	67,6 mm	23,0 mm		36,0 mm	
A55064-16-12	CR	12	19,0 mm	3/4"	16	1 5/16-12	71,4 mm	26,0 mm		38,0 mm	
A55G64-16-12	SN	12	19,0 mm	3/4"	16	1 5/16-12	71,0 mm	24,0 mm	27,0 mm	41,0 mm	NEW
A55064-16-16	CR	16	25,0 mm	1"	16	1 5/16-12	79,4 mm	24,0 mm		38,0 mm	
A55G64-16-16	SN	16	25,0 mm	1"	16	1 5/16-12	80,0 mm	24,0 mm	32,0 mm	41,0 mm	NEW
A55064-20-16	Thrust wire nut	16	25,0 mm	1"	20	1 5/8-12	83,8 mm	37,0 mm		50,0 mm	
A55064-20-20	Thrust wire nut	20	32,0 mm	1 1/4"	20	1 5/8-12	97,1 mm	37,0 mm		50,0 mm	
A55064-24-24	Thrust wire nut	24	38,0 mm	1 1/2"	24	1 7/8-12	112,7 mm	43,0 mm		55,0 mm	
A55064-32-32	Thrust wire nut	32	51,0 mm	2"	32	2 1/2-12	159,9 mm	67,0 mm		70,0 mm	