

// A55A26 - FEMMINA ORFS CON CONTRO - ESAGONO



// A55H26 - FEMMINA ORFS CON DOPPIO ESAGONO E DADO BATTUTA



	СН		C mm	F1 -	F1 Dash Size	ID			N t T	Code
	mm					ln	mm	Dash	Nut Type	Code
m	14,0 mm	17,0 mm	26,8 mm	9/16-18	04	3/16"	5,0 mm	03	CR	A55A26-04-03
m	14,0 mm	17,0 mm	27,3 mm	9/16-18	04	1/4"	6,0 mm	04	CR	A55A26-04-04
m	14,0 mm	17,0 mm	29,5 mm	9/16-18	04	1/4"	6,0 mm	04	SN	A55H26-04-04
m	17,0 mm	22,0 mm	30,3 mm	11/16-16	06	1/4"	6,0 mm	04	CR	A55A26-06-04
m	17,0 mm	22,0 mm	31,8 mm	11/16-16	06	1/4"	6,0 mm	04	SN	A55H26-06-04
m	22,0 mm	24,0 mm	35,3 mm	13/16-16	80	1/4"	6,0 mm	04	CR	A55A26-08-04
m	22,0 mm	24,0 mm	35,8 mm	13/16-16	80	1/4"	6,0 mm	04	SN	A55H26-08-04
m	17,0 mm	22,0 mm	30,3 mm	11/16-16	06	5/16"	8,0 mm	05	CR	A55A26-06-05
m	17,0 mm	22,0 mm	38,0 mm	11/16-16	06	5/16"	8,0 mm	05	SN	A55H26-06-05
m	17,0 mm	17,0 mm	28,3 mm	9/16-18	04	3/8"	10,0 mm	06	CR	A55A26-04-06
m	17,0 mm	22,0 mm	30,3 mm	11/16-16	06	3/8"	10,0 mm	06	CR	A55A26-06-06
m	17,0 mm	22,0 mm	32,3 mm	11/16-16	06	3/8"	10,0 mm	06	SN	A55H26-06-06
m	22,0 mm	24,0 mm	35,3 mm	13/16-16	08	3/8"	10,0 mm	06	CR	A55A26-08-06
m	22,0 mm	24,0 mm	39,3 mm	13/16-16	08	3/8"	10,0 mm	06	SN	A55H26-08-06
m	19,0 mm	22,0 mm	32,1 mm	11/16-16	06	1/2"	13,0 mm	08	CR	A55A26-06-08
m	22,0 mm	24,0 mm	36,1 mm	13/16-16	08	1/2"	13,0 mm	08	CR	A55A26-08-08
m	22,0 mm	24,0 mm	40,5 mm	13/16-16	08	1/2"	13,0 mm	08	SN	A55H26-08-08
m	24,0 mm	30,0 mm	39,6 mm	1-14	10	1/2"	13,0 mm	08	CR	A55A26-10-08
m	24,0 mm	30,0 mm	43,0 mm	1-14	10	1/2"	13,0 mm	08	SN	A55H26-10-08
m	30,0 mm	36,0 mm	42,1 mm	1 3/16-12	12	1/2"	13,0 mm	08	CR	A55A26-12-08
m	30,0 mm	36,0 mm	42,1 mm	1 3/16-12	12	1/2"	13,0 mm	08	SN	A55H26-12-08
m	24,0 mm	24,0 mm	37,1 mm	13/16-16	08	5/8"	16,0 mm	10	CR	A55A26-08-10
m	24,0 mm	30,0 mm	39,6 mm	1-14	10	5/8"	16,0 mm	10	CR	A55A26-10-10
m	27,0 mm	30,0 mm	39,6 mm	1-14	10	5/8"	16,0 mm	10	SN	A55H26-10-10
m	30,0 mm	36,0 mm	42,1 mm	1 3/16-12	12	5/8"	16,0 mm	10	CR	A55A26-12-10
m	30,0 mm	36,0 mm	42,1 mm	1 3/16-12	12	5/8"	16,0 mm	10	SN	A55H26-12-10
-	27,0 mm	30,0 mm	40,1 mm	1-14	10	3/4"	19,0 mm	12	CR	A55A26-10-12
-	30,0 mm	36,0 mm	42,6 mm	1 3/16-12	12	3/4"	19,0 mm	12	CR	A55A26-12-12
m	30,0 mm	36,0 mm	42,6 mm	1 3/16-12	12	3/4"	19,0 mm	12	SN	A55H26-12-12
\dashv	36,0 mm	41,0 mm	48,6 mm	1 7/16-12	16	3/4"	19,0 mm	12	CR	A55A26-16-12
m	36,0 mm	41,0 mm	50,6 mm	1 7/16-12	16	3/4"	19,0 mm	12	SN	A55H26-16-12
m	32,0 mm	36,0 mm	45,4 mm	1 3/16-12	12	1"	25,0 mm	16	CR	A55A26-12-16
\dashv	36,0 mm	41,0 mm	49,4 mm	1 7/16-12	16	1"	25,0 mm	16	CR	A55A26-16-16
\dashv	36,0 mm	41,0 mm	51,4 mm	1 7/16-12	16	1"	25,0 mm	16	SN	A55H26-16-16
	41,0 mm	50,0 mm	50,4 mm	1 11/16-12	20	1"	25,0 mm	16	CR	A55A26-20-16
\dashv	41,0 mm	50,0 mm	52,0 mm	1 11/16-12	20	1 1/4"	32,0 mm	20	CR	A55A26-20-20
\dashv	50,0 mm	60,0 mm	56,5 mm	2-12	24	1 1/4"	32,0 mm	20	CR	A55A26-24-20
-	50,0 mm	60,0 mm	56,5 mm	2-12	24	1 1/2"	38,0 mm	24	CR	A55A26-24-24